



NOTES:

1. UNIT DIMENSIONS: 3.4" H x 16.93" W x 3.5" D
(87mm) x (430mm) x (88.5mm)
2. UNIT WEIGHT: 9.5LBS (4.3kg)
3. SHIPPING DIMENSIONS: 9.8" H x 22.13" W x 7.95" D
(250mm) x (562mm) x (202mm)
4. SHIPPING WEIGHT: 11.7LBS (5.3kg)
5. ALL WIRING IS TO BE IN COMPLIANCE WITH
NATIONAL AND LOCAL ELECTRICAL CODES.

- 1 20 AMP OUTPUT CIRCUIT BREAKER FOR
L6-20R CORD SET
- 2 20 AMP OUTPUT CIRCUIT BREAKER FOR
L6-20R CORD SET
- 3 L6-20R OUTPUT RECEPTACLE CORD SET
- 4 L6-20R OUTPUT RECEPTACLE CORD SET

- 5 20 AMP OUTPUT CIRCUIT BREAKER FOR
L6-20R CORD SET
- 6 20 AMP OUTPUT CIRCUIT BREAKER FOR
L6-20R CORD SET
- 7 L6-20R OUTPUT RECEPTACLE CORD SET
- 8 L6-20R OUTPUT RECEPTACLE CORD SET

- 9 30 AMP MAINTENANCE BYPASS CIRCUIT
BREAKER
- 10 30 AMP INPUT CIRCUIT BREAKER FOR
L14-30P INPUT PLUG
- 11 L14-30P INPUT PLUG

DRAWN BY West/Tao	SHEET NO. 1 OF 1	<p>POD PD5-006</p> <p>OPTION POD FOR GXT5-5000MVRT4UXLN</p>	<div> <div> </div> <div> VERTIV </div> </div>		
CHK BY L. JOHNSON	ECN NO.				
REF. DWG.	ORDER NO.				
DWG. NO. PD5-006		DATE 09/10/19	REV. # 1	1050 DEARBORN DRIVE P.O. BOX 29186 COLUMBUS, OHIO 43229	

FILE NAME: I:\dpgeng\GXT5\SUBMITTALS(E)\Distribution Options\PD5-001-006