



NOTES:

1. UNIT DIMENSIONS:

5.12" H x 16.93" W x 3.35" D
(130mm) x (430mm) x (85mm)

2. UNIT WEIGHT: (4.6kg)

3. SHIPPING DIMENSIONS:

12.99" H x 22.13" W x 10.31" D
(330mm) x (562mm) x (262mm)

4. SHIPPING WEIGHT: (6kg)

5. ALL WIRING IS TO BE IN COMPLIANCE WITH
NATIONAL AND LOCAL ELECTRICAL CODES.

① C19 OUTPUT SOCKET #1

② C19 OUTPUT SOCKET #2

③ C19 OUTPUT SOCKET #3

④ 15 AMP OUTOUT CIRCUIT BREAKER
FOR C19 OUTPUT SOCKET #1 #2 #3

⑤ PROGRAMMABLE C13 OUTPUT SOCKET #4

⑥ 10 AMP OUTOUT CIRCUIT BREAKER
FOR PROGRAMMABLE C13 OUTPUT SOCKET #4

⑦ 15 AMP OUTOUT CIRCUIT BREAKER
FOR PROGRAMMABLE C19 OUTPUT SOCKET #5

⑧ PROGRAMMABLE C19 OUTPUT SOCKET #5

⑨ 63 AMP OUTPUT CIRCUIT BREAKER
FOR HARDWIRE OUTPUT

⑩ 63 AMP MAINTENANCE BYPASS CIRCUIT BREAKER
FOR MAINTENANCE

⑪ 63 AMP BYPASS CIRCUIT BREAKER
FOR INTERNAL BYPASS

⑫ 63 AMP INPUT CIRCUIT BREAKER
FOR HARDWIRE INPUT

DRAWN BY
West
CHK BY
Riley
REF. DWG.

SHEET NO.
1 OF 1
ECN NO.
ORDER NO.

POD
PD5-CE10HDWRMBSU
STANDARD POD FOR GXT5-10KHVRT5UXLN

DWG. NO.
PD5-CE10HDWRMBSU

DATE
16/05/19

REV. #
1

1050 DEARBORN DRIVE
P.O. BOX 29186
COLUMBUS, OHIO 43229



FILE NAME: